



TECHNICAL SPECIFICATIONS

| ARB AIR COMPRESSORS | | SUPPLY VOLTAGE | | PERFORMANCE UNDER NO LOAD | | PERFORMANCE UNDER LOAD | | MAXIMUM LOAD | | WEIGHT | | WEIGHT | | DIMENSIONS | | | | | | AUTOMOTIVE CURRENT LOAD PROTECTION IN LOOM | | AIR LOCKER SOLENOID MOUNTING MANIFOLD | | PRESSURE CUTOUT SWITCH | | DURABLE POLYPROPYLENE CARRY CASE | | AIR FILTER EQUIPPED | | 6 METER [20 FT] TYRE INFLATION HOSE | | THERMAL OVER-LOAD PROTECTED MOTOR | | LOW HEAD SUBMERSIBLE | |
|------------------------|------------------------------|----------------|------|---------------------------|---------------|------------------------|--------------|-----------------------------|----------------------------|---------------------------------------|----------------------------|--------|--------------|------------|------|-----|------|-----|-----|--|--------------|---------------------------------------|------|------------------------|----------------|----------------------------------|----|---------------------|----|-------------------------------------|----|-----------------------------------|--|----------------------|--|
| MODEL | DESCRIPTION | V | A | @ 0kPa lpm | @ 0PSI cfm | A | CURRENT DRAW | AIR FLOW @ 200kPa lpm | AIR FLOW @ 29PSI cfm | DUTY CYCLE (on time / off time) | @ 22°C [72°F] % min/min | A | CURRENT DRAW | kPa | psi | kg | lb | kg | lb | HEIGHT mm | LENGTH in | mm | in | mm | in | mm | in | mm | in | mm | in | | | | |
| CKSA12 | COMPACT ON-BOARD | 12 | 5.5 | 27.7 | 0.98 | 7.5 | 19.7 | 0.70 | 35 | 21/39 | 9.0 | 690 | 100 | 2.4 | 5.3 | 1.5 | 3.3 | 122 | 4.8 | 162 | 6.4 | 88 | 3.5 | x | ✓ | ✓ | x | ✓ | x | x | x | x | | | |
| CKMA12 | HIGH OUTPUT ON-BOARD | 12 | 14.2 | 87.2 | 3.08 | 25.2 | 65.9 | 2.34 | 50 | 30/30 | 32.0 | 690 | 100 | 4.5 | 9.9 | 3.5 | 7.7 | 145 | 5.7 | 190 | 7.5 | 98 | 3.9 | ✓ | ✓ | ✓ | x | ✓ | ✓ | ✓ | ✓ | | | | |
| CKMA24 | HIGH OUTPUT ON-BOARD | 24 | 7.1 | 87.2 | 3.08 | 12.6 | 65.9 | 2.34 | 50 | 30/30 | 18.0 | 690 | 100 | 4.5 | 9.9 | 3.5 | 7.7 | 145 | 5.7 | 190 | 7.5 | 98 | 3.9 | ✓ | ✓ | ✓ | x | ✓ | ✓ | ✓ | ✓ | | | | |
| CKMP12 | HIGH OUTPUT PORTABLE | 12 | 14.2 | 87.2 | 3.08 | 25.2 | 65.9 | 2.34 | 50 | 30/30 | 32.0 | 690 | 100 | 6.6 | 14.5 | N/A | N/A | 208 | 8.2 | 440 | 17.3 | 238 | 9.4 | ✓ | x | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | | | |
| CKMTA12 | MAXIMUM PERFORMANCE ONBOARD | 12 | 28.4 | 174.4 | 6.16 | 50.4 | 131.8 | 4.68 | 100 | 60/0 | 68.6 | 1030 | 150 | 8.8 | 19.4 | 7.9 | 17.4 | 105 | 4.1 | 278 | 10.9 | 190 | 7.5 | ✓ | x ¹ | ✓ | x | ✓ | ✓ | ✓ | ✓ | | | | |
| CKMTA24 | MAXIMUM PERFORMANCE ONBOARD | 24 | 14.2 | 174.4 | 6.16 | 25.2 | 131.8 | 4.68 | 100 | 60/0 | 34.3 | 1030 | 150 | 8.8 | 19.4 | 7.9 | 17.4 | 105 | 4.1 | 278 | 10.9 | 190 | 7.5 | ✓ | x ¹ | ✓ | x | ✓ | ✓ | ✓ | ✓ | | | | |
| CKMTP12 | MAXIMUM PERFORMANCE PORTABLE | 12 | 28.4 | 174.4 | 6.16 | 50.4 | 131.8 | 4.68 | 100 | 60/0 | 68.6 | 1030 | 150 | 15 | 33.0 | N/A | N/A | 186 | 7.3 | 478 | 18.8 | 355 | 14.0 | ✓ | x | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | | | |

¹ Air locker solenoids can be fitted using optional manifold kit #171503

-All ARB Air Compressors are individually leak tested, pressure tested, current draw tested and flow tested under load at the factory before packaging.

-ARB Air Compressor pressure switches are specially designed to suit the working pressure range of an ARB Air Locker air operated locking differential.

-All specifications here are average nominal values recorded during factory testing, and these values may vary as materials technology and component design undergoes continuous improvement.

