

Mud-Terrain T/A KM3 - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
21105	7.50R16/E 116/112Q	Standard	RBL	//	5.5" - 7"	8.7" on 6"	31.8"	654	18.0	2755@80	50.46 lbs
33172	28x10.00R14NHS/8PR Q	Standard	RBL	//	6" - 8.5"	10" on 7"	28.0"	743	18.0	1557@44	36.86 lbs
11882	30x9.50R15/C 104Q	Standard	RBL	//	6.5" - 8.5"	9.5" on 7.5"	29.5"	705	18.0	1985@50	46.32 lbs
76357	30x10.00R14NHS/8PR Q	Standard	RBL	//	6" - 8.5"	10" on 7"	30.0"	693	18.0	1760@44	40.3 lbs
50627	30x10.00R15NHS/8PR Q	Standard	RBL	//	6" - 8.5"	10" on 7"	30.0"	693	18.0	1694@44	39.68 lbs
00893	31x10.50R15/C 109Q	Standard	RBL	//	7" - 9"	10.6" on 8.5"	30.5"	682	18.0	2270@50	51.28 lbs
29937	32x10.00R14NHS/8PR Q	Standard	RBL	//	6" - 8.5"	10" on 7"	32.0"	650	18.0	2002@44	42.55 lbs
40964	32x10.00R15NHS/8PR Q	Standard	RBL	//	6" - 8.5"	10" on 7"	32.0"	650	18.0	1936@44	43.98 lbs
26547	32x11.50R15/C 113Q	Standard	RBL	//	8" - 10"	11.4" on 9"	31.5"	659	18.0	2535@50	55.16 lbs
17109	33x10.50R15/C 114Q	Standard	RBL	//	7" - 9"	10.6" on 8.5"	32.5"	640	18.0	2600@50	56.46 lbs
28830	33x12.50R15/C 108Q	Standard	RBL	//	8.5" - 11"	12.5" on 10"	32.5"	640	18.0	2205@45	59.88 lbs
01898	33x12.50R17/E 120Q	Standard	RBL	//	8.5" - 11"	12.5" on 10"	32.5"	640	18.0	3085@75	67.59 lbs
32589	33x12.50R18/E 118Q	Standard	RBL	//	8.5" - 11"	12.5" on 10"	32.5"	640	18.0	2910@75	69.36 lbs
38937	33x12.50R20/E 114Q	Standard	RBL	//	8.5" - 11"	12.5" on 10"	32.5"	640	18.0	2600@75	67.24 lbs
27226	35x12.50R15/C 113Q	Standard	RBL	//	8.5" - 11"	12.5" on 10"	34.5"	602	18.0	2535@45	66.09 lbs
55079	35x12.50R17/E 121Q	Standard	RBL	//	8.5" - 11"	12.5" on 10"	34.5"	602	18.0	3195@75	74.32 lbs
72204	35x12.50R18/E 123Q	Standard	RBL	//	8.5" - 11"	12.5" on 10"	34.5"	602	18.0	3415@75	72.75 lbs
08843	35x12.50R20/E 121Q	Standard	RBL	//	8.5" - 11"	12.5" on 10"	34.5"	602	18.0	3195@75	74.52 lbs
39458	37x12.50R17/D 124Q	Standard	RBL	//	8.5" - 11"	12.5" on 10"	36.5"	569	18.0	3525@50	77.38 lbs
00958	37x12.50R18/E 128Q	Standard	RBL	//	8.5" - 11"	12.5" on 10"	36.5"	569	18.0	3970@75	78.97 lbs
37549	37x12.50R20/E 126Q	Standard	RBL	//	8.5" - 11"	12.5" on 10"	36.5"	569	18.0	3750@75	79.85 lbs
75495	37x13.50R18/E 128Q	Standard	RBL	//	8.5" - 11"	13.6" on 11"	36.5"	569	18.0	3970@75	80.16 lbs
01047	37x13.50R20/E 127Q	Standard	RBL	//	8.5" - 11"	13.6" on 11"	36.5"	569	18.0	3860@75	82.58 lbs
71004	39x13.50R17/C 121Q	Standard	RBL	//	8.5" - 11"	13.6" on 11"	38.5"	540	18.0	3195@45	87.9 lbs

Mud-Terrain T/A KM3 - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
92296	LT215/75R15/C 100/97Q	Standard	RBL	//	5.5" - 7"	8.5" on 6"	27.7"	751	18.0	1765@50	41.29 lbs
23390	LT235/70R16/D 110/107Q	Standard	RBL	//	6" - 7.5"	9.5" on 7"	29.0"	718	18.0	2335@65	49.16 lbs
09453	LT235/75R15/D 110/107Q	Standard	RBL	//	6" - 7"	9.3" on 6.5"	28.9"	721	18.0	2335@65	47.75 lbs
63794	LT245/70R17/E 119/116Q	Standard	RBL	//	6.5" - 8"	9.8" on 7"	30.6"	681	18.0	3000@80	56.46 lbs
11954	LT245/75R16/E 120/116Q	Standard	RBL	//	6.5" - 8"	9.8" on 7"	30.5"	683	18.0	3042@80	53.9 lbs
09656	LT255/65R17/D 114/110Q	Standard	RBL	//	7" - 9"	10.2" on 7.5"	30.1"	691	18.0	2600@65	54.21 lbs
64691	LT255/70R16/E 120/117Q	Standard	RBL	//	6.5" - 8"	10.2" on 7.5"	30.1"	691	18.0	3085@80	54.78 lbs
43996	LT255/75R17/C 111/108Q	Standard	RBL	//	6.5" - 8.5"	10" on 7"	32.1"	649	18.0	2405@50	54.63 lbs
85538	LT255/85R16/E 123/120Q	Standard	RBL	//	6.5" - 8"	10" on 7"	33.1"	629	18.0	3415@80	59.02 lbs
81901	LT265/60R18/E 119/116Q	Standard	RBL	//	7.5" - 9.5"	10.7" on 8"	30.5"	682	18.0	3000@80	57.43 lbs
50779	LT265/65R17/E 120/117Q	Standard	RBL	//	7.5" - 9.5"	10.7" on 8"	30.6"	681	18.0	3085@80	56.72 lbs
12657	LT265/70R16/E 121/118Q	Standard	RBL	//	7" - 8.5"	10.7" on 8"	30.6"	679	18.0	3195@80	57.76 lbs
32095	LT265/70R17/E 121/118Q	Standard	RBL	//	7" - 8.5"	10.7" on 8"	31.7"	657	18.0	3195@80	59.61 lbs
79327	LT265/75R16/E 123/120Q	Standard	RBL	//	7" - 8"	10.5" on 7.5"	31.7"	657	18.0	3415@80	59.3 lbs
15830	LT275/65R20/E 126/123Q	Standard	RBL	//	7.5" - 9.5"	11" on 8"	34.1"	610	18.0	3750@80	66.84 lbs
10199	LT275/70R18/E 125/122Q	Standard	RBL	//	7" - 8.5"	11" on 8"	33.2"	627	18.0	3640@80	65.19 lbs
63019	LT285/55R20/E 122/119Q	Standard	RBL	//	8" - 10"	11.7" on 9"	32.4"	643	18.0	3305@80	65.1 lbs
53313	LT285/70R17/E 121/118Q	Standard	RBL	//	7.5" - 9"	11.5" on 8.5"	32.8"	635	18.0	3195@80	67.35 lbs
85586	LT285/75R16/E 126/123Q	Standard	RBL	//	7.5" - 9"	11.3" on 8"	32.8"	634	18.0	3750@80	64.46 lbs
17526	LT295/55R20/E 123/120Q	Standard	RBL	//	8" - 10"	12.2" on 9.5"	32.8"	635	18.0	3415@80	67.15 lbs
82008	LT295/60R20/E 126/123Q	Standard	RBL	//	8" - 10"	11.8" on 8.5"	33.9"	613	18.0	3750@80	73.5 lbs
15052	LT295/70R17/E 121/118Q	Standard	RBL	//	7.5" - 10"	11.8" on 8.5"	33.3"	624	18.0	3195@80	68.85 lbs
91993	LT305/55R20/E 121/118Q	Standard	RBL	//	8.5" - 11"	12.4" on 9.5"	33.2"	626	18.0	3195@75	71.61 lbs
84454	LT305/70R16/E 124/121Q	Standard	RBL	//	8" - 9.5"	12.2" on 9"	32.8"	634	18.0	3525@75	68.06 lbs

Mud-Terrain T/A KM3 - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
69713	LT315/70R17/E 121Q	Standard	RBL	//	8" - 11"	12.7" on 9.5"	34.4"	604	18.0	3195@75	73.68 lbs
08056	LT315/75R16/E 127/124Q	Standard	RBL	//	8" - 11"	12.3" on 8.5"	34.6"	602	18.0	3860@75	73.41 lbs
51810	LT325/60R20/E 126/123Q	Standard	RBL	//	9" - 12"	13" on 9.5"	35.4"	588	18.0	3750@75	77.8 lbs